



5/489A Warrigal Road Moorabbin, VIC, 3189
0431 808 725
sales@austechepoxy.com
www.austechepoxy.com

Endurocure®

Description

Endurocure is an acrylic modified emulsion used as a curing membrane on freshly poured concrete. Water based acrylic curing compound conforms to AS3799.

Advantages

- Complies with Australian Standard AS3799
- Water retention efficiency of 90%.
- Water based
- Environmentally friendly
- Dries to a clear finish
- Accepts most after trades

Application

Stir contents thoroughly before using.

Spray Endurocure evenly over the freshly laid concrete as soon as possible after final trowelling just after the disappearance of surface bleed water for maximum water retention (approximately 1 to 2 hours depending on the ambient temperature and atmospheric conditions).

Apply to vertical surfaces immediately after the formwork has been removed.

Apply at an even coverage rate of 15m²/litre.

Ensure the concrete surface is completely free of stains, oils, form coatings etc. to obtain good adhesion of Endurocure and to avoid discoloration or uneven surface effects.

Properties

- Appearance: Milky white emulsion
- Coverage: 15m² per litre
- Viscosity: 20 - 22 seconds
- Solids: 40% +/- 1%
- Solubility in Water: Totally soluble
- Shelf Life: 12 months maximum
- Dry Time: Tack Free: 1 - 3 hours
- Hard Dry: 4 - 8 hours
- Trafficable: 24 hours
- Application Temperature: 10°C - 35°C
- Application By: Spray, Brush, Roller, Broom
- Packaging: - 200 Lt drum
- UN Number: Not applicable
- Hazchem Code: Not applicable
- Packaging Group: Not applicable
- Poison Schedule: Not applicable
- Dangerous Goods Class: Not applicable

Coverage

15 square metres per litre

Cleaning

Endurocure should be removed from tools and equipment with water immediately after use.